

"When Quality Matters"

Ranjos Inc.

Measuring Tapes



Keson fiberglass reinforced tapes are designed to withstand more wear and tear than any other type of measuring tape. These tapes contain more fiberglass strands for greater tensile strength and superior accuracy when tension is applied. Temperature correction is not necessary and a proven dielectric strength of 200,000 V/M is your assurance of safety from electrical hazards.



New Dual-Sided 2-Color Fiberglass Tape Measures -

Two sided color makes graduations easier to identify. White side is always feet and inches, yellow side is 10ths or metric. (Exception: 10ths & metric, 10ths-white side & metric-yellow.) All KESON fiberglass tape measures are double PVC coated to offer greater resistance to wear.

2 tapes we generally have in stock.

NR10200H




Open Type Reel, 10H Series 10ths 200 ft.

OTR1810300


Open Type Reel, 1810 Series

Printed on two sides. One side in feet, inches and 8ths. Second side in feet, 10ths and 100ths. 300 ft.



Perma Clad™ Nylon Coated Steel Tape Measures

Exceptional accuracy for surveyor quality measurements.



Less Wind Drift and Improved Flexibility These nylon coated steel tapes bend easily to curved surfaces and are lightweight even in 300 ft. length. They are constructed to be highly break and damage resistant under the toughest field conditions.

Features:

- ✍ Tough nylon coated steel assures long life under the worst field abuse.
- ✍ Superior accuracy even under temperature extremes.
- ✍ Break-resistant even under severe use in the field.
- ✍ Attractively packaged for consumer appeal.



6852 OLSEN RD PENSACOLA FL. 32506 PH & FAX 850-456-3006 (FREE 888-626-2007)

WWW.RANJOS.COM