

"When Quality Matters"



# The best cones and barrels in the business

## TRI-GLO SERIES

All vinyl construction assures durability and flexibility in all weather conditions. Long lasting brilliant fluorescent color provides high visibility protection. Ultraviolet stabilized color provides maximum resistance to fading. High density base creates low center of gravity for maximum stability. Choose from 6 sizes – 5", 6", 12", 18", 28", 36" – available in various weights and styles to meet specific needs. Engineered to meet MUTCD specifications. Options, such as stenciling, hot stamping, reflective collars, or flag adapters are available.

### Material

One Piece Construction All PVC Cone  
 Base – Black PVC  
 Underliner Pink PVC  
 Top Coat – Highly Pigmented PVC – UV Stabilized  
**Performance**  
 Tensile Strength 1200 psi  
 Elongation 200%  
 Tear Strength 250 lbs/inch  
 Hardness (Conical Section) 75 +/- 5 Shore A  
 Heat Resistance No slump after 8 Hrs. @ 160° F  
 Low Temperature Strength 10 ft/lb @ -5° F

Model No.	Height In./mm	Weight Lbs./kg	Wall Thickness		Dimensions for Cone Diagram		
			Top in.	Bottom in.	A in.	B in.	C in.
0550	5/127	25/11	.050	.075	.75	2.75	4
0650	6/152	.88/40	.060	.075	2	4	6
1250	12/305	1.5/68	.065	.100	2	6.5	8.5
1850	18/457	3/1.36	.065	.120	2.19	7.25	11.5
1850-5	18/457	5/2.27	.075	.125	2.19	7.25	13.75
2825	28/711	5/2.27	.075	.130	1.75	7.5	13
2825-7	28/711	7/3.18	.075	.130	1.75	7.5	13.75
2825-10	28/711	10/4.54	.075	.130	1.75	7.5	15.25
2850	28/711	7/3.18	.075	.130	2.19	10.5	15.25
2850-8	28/711	8/3.63	.075	.130	2.19	10.5	15.25
2850-10	28/711	10/4.54	.075	.130	2.19	10.5	15.25
3650-8	36/914	8/3.63	.075	.130	2.75	10.5	15.25
3650-10	36/914	10/4.54	.075	.130	2.75	10.5	15.25
3650-12	36/914	12/5.44	.080	.130	2.75	10.5	15.25

6852 OLESN RD PENSACOLA, FL. 32506 PH & FAX 850-456-3006 (FREE 888-626-2007)

WWW.RANJOS.COM